TCPDUMP

Command Line Options							
-A	Print frame pay	load in ASCII		-q	Quick output		
-c <count></count>	Exit after capturing count packets			-r <file></file>	Read packets from file		
-D	List available interfaces			-s <len></len>	Capture up to len bytes per packet		
-e	Print link-level headers			-S	Print absolute TCP sequence numbers		
-F <file></file>	Use file as the filter expression			-t	Don't print timestamps		
-G <n></n>	Rotate the dump file every n seconds			-v[v[v]]	Print more verbose output		
-i <iface></iface>	Specifies the capture interface			-w <file></file>	Write captured packets to file		
-K	Don't verify TCP checksums			- x	Print frame payload in hex		
-L	List data link types for the interface			-X	Print frame payload in hex and ASCII		
-n	Don't convert addresses to names			-y <type></type>	Specify the data link type		
-p	Don't capture in promiscuous mode			-Z <user></user>	Drop privileges from root to user		
Capture Filter Primitives							
[src dst] host <host> Matches a host as the IP source, destination, or either</host>							
ether [src dst] host <ehost></ehost>				Matches a host as the Ethernet source, destination, or either			
gateway host <host></host>				Matches packets which used host as a gateway			
[src dst] n	et <network>/</network>	<len></len>	Matches	Matches packets to or from an endpoint residing in network			
[tcp udp] [src dst] port <port> Matches TCP or UDP packets sent to/from port</port>							
[tcp udp] [src dst] port	range <p1>-<p2< th=""><th>Matches</th><th colspan="3">atches TCP or UDP packets to/from a port in the given range</th></p2<></p1>	Matches	atches TCP or UDP packets to/from a port in the given range			
less <length></length>				Matches packets less than or equal to length			
greater <length></length>				Matches packets greater than or equal to length			
<pre>(ether ip ip6) proto <pre><pre>col></pre></pre></pre>				Matches an Ethernet, IPv4, or IPv6 protocol			
(ether ip) broadcast				Matches Ethernet or IPv4 broadcasts			
(ether ip ip6) multicast				Matches Ethernet, IPv4, or IPv6 multicasts			
type (mgt ctl data) [subtype <subtype>]</subtype>				Matches 802.11 frames based on type and optional subtype			
vlan [<vlan>]</vlan>				Matches 802.1Q frames, optionally with a VLAN ID of vlan			
mpls [<label>]</label>				Matches MPLS packets, optionally with a label of label			
<expr> <relop> <expr></expr></relop></expr>			Matches packets by an arbitrary expression				
Protocols		Modifiers		Examples		s	
arp ip6	slip	! or not	udp dst	port not 53		UDP not bound for port 53	
ether lin	k tcp	&& or and	host 10	.0.0.1 && ho	st 10.0.0.2	Traffic between these hosts	
fddi ppp	tr	or or	tcp dst	port 80 or	8080	Packets to either TCP port	
icmp rad	io udp			ICMF	P Types		
ip rar	arp wlan icmp-echoreply		у	icmp-route	radvert	icmp-tstampreply	
TCP Flags		icmp-unreach		icmp-route	rsolicit	icmp-ireq	
tcp-urg tcp-rst		icmp-sourcequench		icmp-timxc	eed	icmp-ireqreply	
tcp-ack tcp-syn		icmp-redirect		icmp-param	prob	icmp-maskreq	
tcp-psh tcp-fin		icmp-echo		icmp-tstam	ıp	icmp-maskreply	

by Jeremy Stretch v2.0